SCHEDULE

" A "

to

BY-LAW #476 (1978)



MINIMUM SPECIFICATIONS FOR FENCING SWIMMING POOLS IN THE TOWN OF PELHAM -

1. CHAIN LINK FENCE: ----

of a minimum height of 1.5m above ground level and a maximum height of 2m above ground level and lower edge maximum 50mm from ground.

Material - Minimum 3.658mm, 50mm wire mesh galvanized after weaving

Posts - Minimum outside diameter of 60mm capped

Post Spacing - Maximum 3m apart

Corner & Terminal Posts - Minimum outside diameter of 89mm capped

Top Rail - Minimum outside diameter 43mm capped

Footings - Concrete, minimum 1m deep

------ or ------

2. ORNAMENTAL FENCE: ----

of a minimum height of 1.5m above ground level and a maximum height of 2m above ground level, bottom rail maximum 50mm above ground

Material - Vertical bars minimum spacing 100mm

Posts - Minimum 38mm square, solid

Post Spacing - Maximum 225m apart

Top & Bottom Rail - Minimum 25 x 25 x 3mm angle

Footings, Concrebe slab or footings, minimum 1m deep

or -----

3. WOOD OR PLASTIC FENCE: ----

of a minimum height of 1.5m above ground level and a maximum height of 2m above ground level, bottom rail maximum 50mm above ground

Material - Vertical wood slats

 Wood or plastic, braced horizontally by top and bottom rail

Bracing - Wood - Minimum 38mm x 89mm

- Pipe - Minimum 43mm, O.D.

Posts - Wood - Minimum 89mm x 89mm

- Iron Minimum 38mm square of solid material
- Pipe Minimum 60mm outside diameter

Post Spacing - Maximum 3m apart

Footings - Concrete slab or footings, minimum Im deep

4. GATES: ----

of a minimum height of 1.5m above ground level and a maximum height of 2m above ground level, bottom rail maximum 50mm above ground

SCHEDULE "A" TO BY-LAW #476 (1978) - (con't)

Der &

Fences shall be equipped with not less than one gate of a design and material similar to fencing used. Each gate shall be equipped with an automatic closing device, and shall be kept locked at all times except when the swimming pool is in actual use by the owner of the property, or his duly authorized agents.